



PASSPORT LAMINATOR MODEL 6041P

The **ASP 6041P Passport Laminator** is a simple to operate machine which has been specially designed to apply a heat sealable Security Laminate to the inside pages of a passport through the application of both heat and pressure.

The special Security Laminate coated with a temperature activated adhesive is placed on the top of the page to be protected and the closed book is inserted into the Laminator. The book is automatically transported through rollers within the machine which are preset at the correct temperature and pressure to enable the adhesive to melt and be applied securely to the page.

Once processed, the book is ejected from the Laminator.

**Authorized Distributor: HS TRADE a.s., Nad Rokoskou 19, 182 00 Praha 8,
Czech Republic; website: www.hstrade.cz
contact: Jan Hejkrlik, cell phone: +420 602 355 569
email: hejkrlik.jan@hstrade.cz**



A S P PASSPORT LAMINATOR

MODEL 6041P

DATA SHEET

<i>DIMENSIONS</i>	:	<i>340mm x 260mm x 115mm</i>
<i>WEIGHT</i>	:	<i>6.5 Kilograms</i>
<i>TEMPERATURE RANGE</i>	:	<i>10 - 285 Degrees Celsius</i>
<i>SUPPLY VOLTAGE</i>	:	<i>110 - 120 Vac, 50 / 60 Hz</i> <i>or</i> <i>220 - 240 Vac, 50 / 60 Hz</i>
<i>THERMOSTAT CONTROL</i>	:	<i>Solid State</i>
<i>THROUGHPUT</i>	:	<i>30 – 40 Seconds per Book</i>
<i>SWITCHES & RUN (ON/OFF)</i>	:	<i>2 X 2 Way for HEAT (ON/OFF)</i>
<i>TEMPERATURE GAUGE</i>	:	<i>External - Side Mounted for Easy Access</i>
<i>TEMPERATURE ADJUSTMENTS</i>	:	<i>Via Single Control</i>
<i>PRESSURE</i>	:	<i>Via Simple Tension Adjustment</i>

Optimum Temperature and Pressure settings are usually set at the time of manufacture to account for particular combinations of laminate, Adhesive and Book Thickness (Sample books are required at time of order)

(HS TRADE reserves the right to change the above specifications without prior notification)

**Authorized Distributor: HS TRADE a.s., Nad Rokoskou 19, 182 00 Praha 8,
Czech Republic; website: www.hstrade.cz
contact: Jan Hejkrlik, cell phone: +420 602 355 569
email: hejkrlik.jan@hstrade.cz**